CGI420 / CGI420R 4 to 20mA Interface



The (CGI420) and (CGI420R) are 4 to 20mA intelligent addressable modules designed to interface with gas detection modules and are compatible with Eaton intelligent addressable control panels.

These interfaces have a unique address on the loop and built in isolator for loop short circuit protection.

Each of the DIL switches JP1, JP2 and JP3 can be programmable to set the threshold level for prealarm1, pre-alarm 2 and alarm respectively.

This can be expressed as a percentage of L.E.L (lower explosion limit) or PPM (parts per million).

Features and Benefits

- Soft addressed
- Integral short circuit isolator
- Single address
- Ideal interface for gas detection modules
- 3 volt free outputs for each of the 3 alarm levels (optional)
- Requires external power supply
- The supply to the gas detector is taken directly from the interface
- Programmable levels of sensitivity

Catalogue numbers

Description	Code
4 to 20mA Interface	CGI420
4 to 20mA Interface (relay output)	CGI420R



Eaton Electrical Sector EMEA Route de la Longeraie 7 1110 Morges, Switzerland

Eaton

Fire Systems Business Cooper Lighting and Safety Ltd Wheatley Hall Road Doncaster South Yorkshire DN2 4NB United Kingdom Tel: +44 (0)1302 303 999 Fax: +44 (0)1302 303 333 Email: sales@cooperfire.com Web: www.cooperfire.com

© 2014 Eaton All Rights Reserved Pub Reference: F-DS019 October 2014 Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to Trademarks. The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

Eaton is a registered trademark. All other trademarks are property of their respective owners.